



中国认可
检验
INSPECTION
CNAS IB0071



NO.262640108989

SAFETY DATASHEET

Product Name: Rechargeable Lithium-ion Cell
INR21700-RS50 5000mAh 3.60V 18Wh

Effective Date: 2026-02-14

Compiler: Chen Yushuang

Checker: Liu Wangqing

Approver: Dongxuesheng



Shanghai Institute of Chemical Industry Testing Co., Ltd.



声 明

Statement

1. 本报告无上海化工院检测有限公司检验检测专用章、二维码无效。
The report is invalid if it is not affixed the dedicated inspection and testing seal of Shanghai Institute of Chemical Industry Testing Co., Ltd. and QR Code on it.
2. 本报告复印件无效。
Copies of the report are invalid.
3. 本报告无编制、审核、批准人签字无效。
The report is invalid without the signatures of compiler, checker and approver.
4. 本报告涂改无效。
The report is invalid if it is forged or altered.
5. 本报告中的检验结论仅适用于收到的样品。
The inspection conclusion of this report only applies to the sample as received.
6. 除另有说明，检测检验类别都是指委托分析。
Unless noted otherwise, the test type is consignment test.
7. 本报告的真伪性可登入本公司网站 <http://www.ghs.cn> 查询
The authenticity of the report can be checked via our website: <http://www.ghs.cn>.

地址：上海市光复西路 2779 号接待大厅

Address: No.2779 West Guangfu Road, Shanghai, China

邮政编码(Post Code): 200062

电话(Tel): (021) 31015134

网址 (web site): www.ghs.cn

电子信箱(E-mail): sds@ghs.cn

Jiangsu Reliance Energy Tech. Co., Ltd.

SAFETY DATA SHEET

Rechargeable Lithium-ion Cell INR21700-RS50

5000mAh 3.60V 18Wh

SECTION1 IDENTIFICATION

Product name: Rechargeable Lithium-ion Cell INR21700-RS50 5000mAh 3.60V 18Wh
Company: Jiangsu Reliance Energy Tech. Co., Ltd.
Address: No. 66, Zhufeng Road, Xinbei District, Changzhou, Jiangsu Province, China
E-mail: yao.hd@reliance-battery.com
Fax: /
Emergency Phone: 051969887551
Recommend use of the chemical and restrictions on use: /
SDS Number: 262640108989
Effective Date: 2026-02-14

SECTION2 HAZARDS IDENTIFICATION

The product is outside of the scope of GHS system.

Main Hazards:

Fire or Explosion Hazards:

Lithium ion battery contains flammable liquid electrolyte that may vent, ignite and produce sparks when subjected to high temperatures (>150℃), when damaged or abused (e.g., mechanical damage or electrical overcharging). May burn rapidly with flare-burning effect. May ignite other batteries in close proximity.

Health Hazards:

Contact with battery's electrolyte may be irritating to skin, eyes and mucous membranes. Fire will produce irritating, corrosive and/or toxic gases. Fumes may cause dizziness or suffocation.

SECTION3 INFORMATION ON INGREDIENTS

Product name: Rechargeable Lithium-ion Cell INR21700-RS50 5000mAh 3.60V 18Wh

Ingredient	Concentration(%)	CAS NO.	EC NO.
Transition metal oxide composites of lithium	20-50	12190-79-3/1203	
		1-65-1/12057-17	235-362-0/620-400-4/601-724-
		-9/182442-95-1/	5/695-690-9/803-110-4
		193214-24-3	
Graphite, Silicon based negative electrode	10-30	7782-42-5/10097	231-955-3/233-232-8
		-28-6	
Iron, aluminum substrate	10-20	7439-89-6/7429-	231-096-4/231-072-3
		90-5	
Ethyl acetate, Dimethyl carbonate, Ethylene carbonate, Lithium hexafluorophosphate	5-15	141-78-6/616-38	205-500-4/210-478-4/202-510-
		-6/96-49-1/2132	
		4-40-3	
			0/244-334-7
Negative substrate copper	3-15	7440-50-8	231-159-6
Composite materials (PET, PI, PE)	0-5	25038-59-9/4979	607-507-1/691-837-6/618-339-
		26-97-3/9002-88	
		-4	
			3

SECTION4 FIRST-AID MEASURES**Skin Exposure:**

If in contact with the internal materials of battery, remove the contaminated clothing, shoes and socks, immediately flush with plenty of water for at least 20 minutes. Call a physician.

Eye Exposure:

In case of the internal battery's materials in contact with eyes, lift your eyelids immediately and rinse them with running water for more than 20 minutes. If irritation persists, call a physician.

Inhalation Exposure:

If inhaled the internal battery's materials, immediately remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Call a physician.

Oral Exposure:

If swallowed the internal battery's materials, do not induce vomiting. Call a physician immediately.

Most Important Symptoms/Effects, Acute and Delayed:

No data available.

Indication of Immediate Medical Attention and Special Treatment Needed, if Necessary:

No data available.

SECTION5 FIRE FIGHTING MEASURES**Suitable Extinguishing Media:**

Suitable: Water spray or regular foam.

Specific Hazards Arising from the Chemical:

May decompose upon combustion to generate irritating, corrosive or toxic fumes. Fumes may cause dizziness or suffocation.

Special Protective Action for Fire-fighters:

Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Fire-extinguishing work is done from the windward. Uninvolved persons should evacuate to a safe place.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures:

Use personal protective equipment. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Entry to noninvolved personnel should be controlled around the leakage area by roping off. Remove all sources of ignition.

Environmental Precautions:

Avoid leakage enter the earth, ditches or waters. Avoid directly release the cleaning waste water into the environment.

Methods and Materials for Containment and Cleaning up:

If the electrolyte leaks, use soil, sand or other non-combustible materials to absorb. The leaked batteries and dirty adsorbents should be placed in metal containers.

SECTION 7 HANDLING AND STORAGE

Precautions for Safe Handling:

Operators should be trained and strictly abide by operating procedures. Wear appropriate protective clothing and safety gloves. Keep away from ignition sources, heat and flame. No smoking at working site. Handling is performed in a well ventilated place. Avoid disassembling the battery at will and reversing battery polarity within the battery assembly. Such batteries must be packed in inner packaging in such a manner as to effectively prevent short circuits and to prevent movement which could lead to short circuits. In case of leakage of the material in the battery, avoid directly contact with eyes and skin. Avoid inhalation. Incompatibilities: Strong oxidizing agents, Combustible materials and Corrosives.

Conditions for Safe Storage, Including Any Incompatibilities:

Store in a cool, dry, and well-ventilated area. Keep away from ignition sources, heat and flame. Incompatibilities: Strong oxidizing agents, Combustible materials and Corrosives. Such batteries must be packed in inner packaging in such a manner as to effectively prevent short circuits and to prevent movement which could lead to short circuits. Storage place should be equipped with appropriate varieties and quantities of fire fighting equipment and leakage emergency treatment equipment.

SECTION 8 EXPOSURE CONTROL/PPE

Control Parameters :

GBZ 2.1-2019 Occupational Exposure Limits for Hazardous Agents in the Workplace - Part 1:
Cobalt and compounds, as Co PC-TWA 0.05mg/m³ PC-STEL 0.1mg/m³ Remarks G2B; Sensitization
Manganese and inorganic compounds, as MnO₂ PC-TWA 0.15mg/m³

Soluble nickel compounds PC-TWA 0.5mg/m³ Remarks G1(Nickel compounds), Sensitization
 Graphite dust PC-TWA(Total dust) 4mg/m³ PC-TWA(Inhalable dust) 2mg/m³
 Aluminum dust: Metal & alloys dust PC-TWA(Total dust) 3mg/m³
 Polyethylene dust PC-TWA(Total dust) 5mg/m³
 Copper, as Cu Copper dust PC-TWA 1 mg/m³ Copper fume PC-TWA 0.2mg/m³
 ACGIH:

Aluminum TLV-TWA 1 mg/m³, R

Graphite, natural TLV-TWA 2 mg/m³, R

Copper dusts and mists TLV-TWA 1 mg/m³ Copper fume TLV-TWA 0.2mg/m³

Appropriate Engineering Controls:

Mechanical exhaust required. Safety shower and eye bath.

Individual Protection Measures:

Eye/Face Protection:

Wear chemical safety glasses if needed.

Skin Protection:

Hand Protection: Wear safety gloves.

Body Protection: Wear appropriate protective clothing.

Respiratory Protection:

Wear government approved respirator if needed.

Thermal Hazards:

No data available.

Other Protect:

No smoking, drinking and eating at working site. Wash thoroughly after handling.

SECTION9 PHYSICAL/CHEMICAL PROPERTIES

Appearance: Gray Cylinder plastics film shell

Odor: Odorless

pH Value: 8-9

Solubility: partial soluble in water

Melting Point/Freezing Point: >300°C

Boiling Point, Initial No data available.

Boiling Point and

Boiling Range:

Flash Point(Closed No data available.

Cup):

Density/Relative No data available.

Density:

Kinematic Viscosity: No data available.

Lower/Upper Explosion Limit/Flammability Limit: No data available.

Vapour Pressure: No data available.

Relative Vapor Density: No data available.

Partition Coefficient N-Octanol/Water (Log Value): No data available.

Autoignition Temperature: No data available.

Decomposition Temperature: No data available.

Particle Characteristics: No data available.

Flammability (Solid, Gas): No data available.

SECTION10 STABILITY AND REACTIVITY

Reactivity:

No data available.

Chemical Stability:

Stable under normal temperatures and pressures.

Possibility of Hazardous Reactions:

No data available.

Conditions to Avoid:

Avoid misoperation, exposure to heat and open flame. Avoid mechanical or electrical abuse and overcharge. Prevent short circuits. Prevent movement which could lead to short circuits.

Incompatible Materials:

Strong oxidizing agents, Combustible materials and Corrosives.

Hazardous Decomposition Products:

Carbon oxides, metal oxides, etc.

SECTION11 TOXICOLOGICAL INFORMATION

Acute Toxicity:

No data available.

Skin Corrosion/Irritation:

The electrolyte in the battery causes skin irritation.

Serious Eye Damage/Irritation:

The electrolyte in the battery causes eye irritation.

Respiratory Sensitization:

No data available.

Carcinogenicity:

No data available.

Skin Sensitization:

No data available.

Germ Cell Mutagenicity:

No data available.

Reproductive Toxicity:

No data available.

Specific Target Organ Toxicity –Single Exposure:

No data available.

Specific Target Organ Toxicity –Repeated Exposure:

No data available.

Aspiration Hazard:

No data available.

SECTION12 ECOLOGICAL INFORMATION

Toxicity:

No data available.

Persistence and Degradability:

No data available.

Bioaccumulative Potential:

No data available.

Mobility in Soil:

No data available.

Other Adverse Effects:

No data available.

SECTION13 DISPOSAL CONSIDERATION

Disposal Methods:

The disposal of discarded battery shall comply with the requirements of relevant laws, regulations, policies and standards such as the "Law of the People's Republic of China on the Prevention and Control of Environmental Pollution by Solid Waste" and "Technical Policy for the Prevention and Control of Waste Battery Pollution". Contact a licensed professional waste disposal service to dispose of wastes. Used battery being transported for disposal or reclamation should be carefully checked prior to shipment to ensure the integrity of each battery and its suitability for transport.

SECTION14 TRANSPORT INFORMATION

Only Lithium Battery
during Transport:

The product has passed the test items of Manual of Tests and Criteria Section 38.3 and UN Model Regulations, SP188, 1.2m drop test. The total net weight of the Lithium batteries is less than 10 kg.

**RID/ADR(2025
Edition):**

The product is not subject to the other provisions of RID/ADR according to special provision 188.

According to 2.2.9.1.7(g), Manufacturers and subsequent distributors of cells or batteries manufactured shall make available the test summary as specified in the Manual of Tests and Criteria, Part III, sub-section 38.3, paragraph 38.3.5.

**IATA DGR(67th
Edition):**

Hazard Class: 9

UN Number: UN3480

Proper Shipping Name: Lithium ion batteries

The product shall meet the General Requirements and section IB of Packaging Instruction 965.

The package must be capable of withstanding the stacking test required in PI 965- IB.

According to 3.9.2.6.1(g), Manufacturers and subsequent distributors of cells or batteries manufactured after 30 June 2003 shall make available the test summary as specified in the Manual of Tests and Criteria, Part III, sub-section 38.3, paragraph 38.3.5.

**IMO IMDG CODE(2024
Edition):**

The product is not subject to the other provisions of IMO IMDG CODE according to special provision 188.

According to 2.9.4.7, Manufacturers and subsequent distributors of cells or batteries manufactured shall make available the test summary as specified in the Manual of Tests and Criteria, Part III, sub-section 38.3, paragraph 38.3.5.

SECTION15 REGULATORY INFORMATION

Domestic Regulations:

Only Lithium Battery during Transport:

The product has passed the test items of Manual of Tests and Criteria Section 38.3 and UN Model Regulations, SP188, 1.2m drop test. The total net weight of the Lithium batteries is less than 10 kg.

Regulations Concerning Road Transportation of Dangerous Goods(JT/T 617-2018):

UN Number: UN3480

Name and Description: Lithium ion batteries

The product is not subject to JT/T 617-2018 according to special provision 188.

List of Dangerous Goods(GB 12268-2025):

UN Number: UN3480

Proper Shipping Name: Lithium ion batteries

The product is not subject GB 12268-2025 according to special provision 188.

List of Dangerous Goods by Rail(TB/T 30006-2022):

Number: 91045



END OF REPORT