




#### SPECIFICATIONS:

1	TYPE:	Protected Li-ion Rechargeable Battery	
2	MODEL NUMBER:	P1634U2	
3	BATTERY CAPACITY:	Nom.1000mAh discharge at 0.2C Min. 980mAh discharge at 0.2C	
4	NOMINAL VOLTAGE:	3.0V	
5	RATED ENERGY:	3000mWh	
6	<b>CHARGE BY TYPE C USB</b>		
	INPUT CHARGE VOLTAGE:	5.0±0.5V	
	INPUT CHARGE CURRENT:	≥ 0.5A	
	USB INTERNAL CURRENT (CC):	330±50mA	RED LIGHT ON
	USB INTERNAL VOLTAGE (CV):	4.20±0.05V	
	USB FULL CHARGE CUT OFF CURRENT:	< 35mA	BLUE LIGHT ON RED LIGHT OFF
7	<b>CHARGE BY LITHIUM-ION BATTERY SPECIALIZED CHARGER ONLY</b>		
	CHARGE LIMIT VOLTAGE:	5.0V	Built in charging circuit
	CHARGE UPPER VOLTAGE:	5.5V	Built in charging circuit
	STANDARD CHARGE CURRENT:	200mA	
	MAXIMUM CHARGE CURRENT:	200mA	
8	STANDARD DISCHARGE CURRENT:	200mA	
9	DISCHARGE END VOLTAGE:	0V	
10	MAXIMUM CONTINUOUS DISCHARGE CURRENT:	2A	
11	MAXIMUM SIZE:	16.9(D)X34.9(L)mm	
12	MAXIMUM WEIGHT:	20g	
13	OPERATION TEMPERATURE:	0°C~+45°C	CHARGE
		-20°C~60°C	DISCHARGE
14	STORAGE TEMPERATURE:	-20°C~+50°C	Less than 1 month
		-20°C~+40°C	Less than 3 months
		-20°C~+25°C	Less than 1 year

#### CAUTION:

- Do not short circuit the battery or dispose of in fire.
- Do not immerse the battery in water or other liquids.
- Do not disassemble.
- Keep the battery out of reach of children.

TEM NO.	DESCRIPTION	QTY.	REVISIONS				 <b>KEEPPower TECHNOLOGY CO., LIMITED</b> www.keeppower.com info@keeppower.com +86 769 82953418		
			REV.	DESCRIPTION	DATE	APPROVED			
1	Cell 16300-E95	1					CHECKED		
2	Safety Circuit-PCM With Micro USB	1	A0	DP-111320-10M001	2025/04/03	Ray	P1634U2 RCR123A 3V 1000mAh 3000mWh Battery		
3	Label P1634U2	1					PART NUMBER	SIZE	SHEET
4	Button Top	1					P1634U2	A4	1 OF 1