



Accessories



X3-Matebox G2

We get rid of complicated wiring work by laying all the wires in the Matebox. All you need to do is just to connect all the cables which are already well-sorted in the Matebox. This helps to save time and money.



X3-Matebox G2

ON-GRID (INVERTER)	
Rated voltage, frequency	380 / 400 / 415 Vac, 50 / 60 Hz
Max.apparent on-grid input/output power	16500 VA
Max. on-grid current	32 A
OFF-GRID (INVERTER)	
Rated voltage, frequency	380 / 400 / 415 Vac, 50 / 60 Hz
Max.apparent off-grid input/output power	15000 VA
Max. off-grid current	25 A
GRID (UTILITY)	
Rated grid voltage, frequency	380 / 400 / 415 Vac, 50 / 60 Hz
Max. current	63 A
LOAD	
Rated voltage, frequency	380 / 400 / 415 Vac, 50 / 60 Hz
Max. current	63 A
ENVIRONMENT LIMIT	
Ingress protection	IP65
Protection class	Class I
Operation temperature range	-25 ~ 60°C (> 45°C derating)
Storage temperature	-40~+70°C
Relative humidity	0~100% RH (condensing)
Max. operation altitude	3000 m
Overvoltage category	III(AC)
OTHER	
Cooling concept	Natural cooling
DIMENSION AND WEIGHT	
Dimensions(WxHxD)	549 × 360 × 192 mm
Net weight	13.5 kg